



农业胎 (AGRICULTURAL TYRE)



PATTERN CODE: **T-151**
 TYRE SIZE: 4.00-19 5.00-15 5.50-16
 6.00-16 6.00-19 6.50-16
 7.50-16 7.50-18 9.00-16
 10.00-16 11.00-16

PATTERN CODE: **T-155**
 TYRE SIZE: 7.00-12 T/L 10.0/80-12 T/L
 10.0/75-15.3 T/L
 11.5/80-15.3 T/L
 12.5/80-15.3 T/L
 10.5/80-18 T/L
 12.5/80-18 T/L
 13.0/65-18 T/L

PATTERN CODE: **T-156**
 TYRE SIZE: 7.50-18 6.50-20

PATTERN CODE: **T-154**
 TYRE SIZE: 4.50-19 10.5/80-18 T/L
 12.0/75-18 T/L
 12.5/80-18 T/L

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)	RELATIVE PRESSURE(bar)
			SECTION WIDTH	OVERALL DIA.		
4.00-19	4	3.00D	112	712	355	3.4
4.50-19	4	3.00D	122	736	387	3.1
5.00-15	4	4J	140	655	365	2.8
5.50-16	6	4.00E	150	710	530	3.7
6.00-16	6	4.50E	165	735	560	3.3
6.00-19	6	4.50E	165	814	650	3.3
6.50-16	6	5.50E	175	760	615	3.1
7.50-16	8	5.50F	205	805	875	3.7
7.50-18	8	5.50F	205	860	950	3.7
9.00-16	10	6.00F	234	855	1250	3.9
10.00-16	10	W8L	274	895	1360	3.4
11.00-16	10	W10L	315	965	1500	3.1
7.00-12 T/L	6	5.50F	200	667	680	2.5
6.50-20	8	5.50F	180	860	865	4.2
10.0/8.0-12 T/L	8	9.00	264	710	1250	3.1
10.0/75-15.3 T/L	10	9.00	264	760	1550	3.9
	12				1700	4.7
	14				1900	5.5
11.5/80-15.3 T/L	10	9.00	290	845	1755	3.4
	12				1962	4.1
	14				2187	4.8
12.5/80-15.3 T/L	14	9.00	307	889	2385	4.3
10.5/80-18 T/L	10	W9	274	907	1360	3.7
12.0/75-18 T/L	12	9.00	299	937	1700	4.0
12.5/80-18 T/L	12	9.00	308	987	1850	3.7
	14				3000	3.7
13.0/65-18 T/L	16	11.00	336	912	2520	4.3



PATTERN CODE: **M101**
TYRE SIZE: 9.00-20 10.00-20 11.00-20



PATTERN CODE: **M102**
TYRE SIZE: 6.50-16 7.00-16 7.50-16
8.25-16 9.00-16 9.00-20
10.00-20 11.00-20



PATTERN CODE: **M103**
TYRE SIZE: 6.50-16 7.00-16 7.50-16
8.25-16 9.00-16



PATTERN CODE: **M103A**
TYRE SIZE: 7.50-16 8.25-16
10.00-20 11.00-20



PATTERN CODE: **M105**
TYRE SIZE: 6.00-15 6.50-15 6.50-16
7.00-15 7.00-16 7.50-15
7.50-16 8.25-16

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)		RELATIVE PRESSURE(kPa)	
			SECTION WIDTH	OVERALL DIA.	SINGLE	DUAL	SINGLE	DUAL
6.00-15	10	4.50E	170	705	825	730	530	530
6.50-15	10	4.50E	180	730	950	825	530	530
6.50-16	14	5.50F	185	750	1060	925	630	630
7.00-15	12	5.50F	200	750	1150	1030	630	630
7.00-16	14+	5.50F	200	775	1320	1180	630	630
7.50-15	14	6.00G	215	780	1450	1285	730	730
7.50-16	16	6.00G	215	805	1500	1320	730	730
7.50-16	18	6.00G	215	816	1650	1500	770	770
8.25-16	16	6.50H	235	855	1800	1600	730	730
8.25-16	18	6.50H	235	867	1800	1600	730	730
9.00-16	18	6.50H	255	890	2120	1850	730	730
9.00-20	16	7.0	259	1018	2900	2500	880	810
9.00-20	18	7.0	259	1038	2900	2500	880	810
10.00-20	16	7.5	278	1055	3000	2650	810	740
10.00-20	18	7.5	278	1073	3350	2900	910	840
11.00-20	18	8.0	293	1085	3650	3150	910	840



轻卡胎 (LIGHT TRUCK TYRE)



PATTERN CODE: **TP334**
TYRE SIZE: 7.50-16



PATTERN CODE: **TP338**
TYRE SIZE: 7.00-16



PATTERN CODE: **TP3341**
TYRE SIZE: 7.00-15



PATTERN CODE: **TP332**
TYRE SIZE: 6.50-14



PATTERN CODE: **TP333**
TYRE SIZE: 6.00-14 6.50-16 7.00-16



PATTERN CODE: **TP3351**
TYRE SIZE: 7.50-16



PATTERN CODE: **TP339**
TYRE SIZE: 8.25-16



PATTERN CODE: **TP3311**
TYRE SIZE: 7.50-16

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)		RELATIVE PRESSURE((kPa)	
			SECTION WIDTH	OVERALL DIA.	SINGLE	DUAL	SINGLE	DUAL
6.00-14	8	4 1/2 J	170	680	685	600	420	420
6.50-14	8	4 1/2 J	180	705	785	690	420	420
6.50-15	8	4.50E	180	730	820	720	420	420
7.00-15	10	5.50F	200	750	1040	915	530	530
	10				975	860	530	530
6.50-16	12	5.50F	185	750	1060	925	630	630
	10				1100	965	530	530
7.00-16	12	5.50F	200	775	1220	1075	630	630
	14				1320	1180	730	730
	10				1260	1105	530	530
7.50-16	12	6.00G	215	805	1405	1240	630	630
	14				1500	1320	730	730
	14				1705	1500	630	630
8.25-16	16	6.50H	235	855	1800	1600	730	730



PATTERN CODE: **TP3381**
 TYRE SIZE: 7.50-20 8.25-20
 9.00-20 10.00-20
 11.00-20



PATTERN CODE: **TP3332**
 TYRE SIZE: 8.25-20 10.00-20
 11.00-20 12.00-20



PATTERN CODE: **TP3333**
 TYRE SIZE: 9.00-20 10.00-20 11.00-20



PATTERN CODE: **M10**
 TYRE SIZE: 11.00-20 12.00-20

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)		RELATIVE PRESSURE(kPa)	
			SECTION WIDTH	OVERALL DIA.	SINGLE	DUAL	SINGLE	DUAL
7.50-20	14	6.0	215	935	1885	1655	810	740
8.25-20	14	6.5	235	974	2205	1940	810	740
	16				2430	2180	910	840
9.00-20	14	7.0	259	1018	2575	2255	770	700
	16				2900	2500	880	810
10.00-20	14	7.5	278	1055	2740	2405	700	630
	16				3000	2630	810	740
11.00-20	16	8.0	293	1085	3350	2900	810	740
	18				3650	3150	910	840
12.00-20	18	8.5	215	1125	3730	3270	810	740



PATTERN CODE: **BS18**
 TYRE SIZE: 10.00R20 11.00R20
 12.00R20



PATTERN CODE: **BS28**
 TYRE SIZE: 9.00R20 10.00R20
 11.00R20 12.00R20



PATTERN CODE: **BS29**
 TYRE SIZE: 10.00R20 11.00R20
 12.00R20

TYRE SIZE	PR	LOAD INDEX	STANDARD RIM	INFLATED TYRE DIA.(mm)		RELATIVE PRESSURE(kPa)		MAX.LOAD(kg)	
				SECTION WIDTH	OVERALL DIA.	SINGLE	DUAL	SINGLE	DUAL
9.00R20	16	144/142	7.0	259	1018	900	900	2800	2650
10.00R20	18	149/146	7.5	278	1055	930	930	3250	3000
11.00R20	18	152/149	8.0	293	1085	930	930	3550	3250
12.00R20	18	154/149	8.5	315	1125	840	770	3790	3270



工业胎 (INDUSTRIAL TYRE)



PATTERN CODE: **TP3312**
 TYRE SIZE: 5.00-8 6.00-9 6.00-15
 6.50-10 7.00-9 7.00-12
 7.00-15 7.50-15 8.25-12
 8.25-15 28x9-15

PATTERN CODE: **TP3314**
 TYRE SIZE: 10-16.5 T/L 12-16.5 T/L

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)	RELATIVE PRESSURE(kPa)
			SECTION WIDTH	OVERALL DIA.		
5.00-8	10	3.50D	137	470	970	1000
6.00-9	10	4.00E	160	540	1275	860
6.00-15	10	4.50E	170	705	1845	830
6.50-10	10	5.00F	175	590	1400	790
7.00-9	10	5.00S	190	590	1685	860
7.00-12	12	5.00S	190	676	2005	860
7.00-15	12	5.5	200	750	2870	860
7.50-15	12	6.0	215	780	3075	790
8.25-12	12	6.5	235	765	3060	720
8.25-15	14	6.5	235	840	3775	830
28x9-15	14	7.0	220	710	3050	970
10-16.5 T/L	10	8.25	266	780	2065	520
12-16.5 T/L	12	9.75	308	857	2760	550



PATTERN CODE: **M778**
 TYRE SIZE: 6.00-9 6.50-10 28x9-15
 8.25-12

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)	RELATIVE PRESSURE(kPa)
			SECTION WIDTH	OVERALL DIA.		
6.00-9	10	4.00E	160	540	1275	860
6.50-10	10	5.00F	175	590	1400	790
28x9-15	14	7.0	220	706	3050	970
8.25-12	12	6.5	210	728	3060	720

拖车胎 (ST TYRE)



PATTERN CODE: **N-622**
 TYRE SIZE: ST175/80D-13 T/L ST205/75D-14 T/L
 ST215/75D-14 T/L ST205/75D-15 T/L
 ST225/75D-15 T/L

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)	RELATIVE PRESSURE(PSI)
			SECTION WIDTH	OVERALL DIA.		
ST175/80D-13 T/L	6	5.50	177	610	1360	50
ST205/75D-14 T/L	6	5.50	203	664	1760	50
ST215/75D-14 T/L	6	6.00	216	678	1870	50
ST205/75D-15 T/L	6	5.50	203	689	1820	50
ST225/75D-15 T/L	8	6.00	223	719	2540	65

真空轻卡胎 (LIGHT TRUCK TUBELESS TYRE)



PATTERN CODE: **M-218**
 TYRE SIZE: 7.00-15 T/L 7.50-16 T/L

TYRE SIZE	PR	STANDARD RIM	INFLATED TYRE DIA.(mm)		MAX.LOAD(kg)		RELATIVE PRESSURE(bar)	
			SECTION WIDTH	OVERALL DIA.	SINGLE	DUAL	SINGLE	DUAL
7.00-15 T/L	8	5.50F	200	750	925	825	4.1	4.1
7.50-16 T/L	10	6.00G	215	805	1250	1120	5.2	5.2