



轻卡胎

LIGHT TRUCK TYRE



HS228



曲线花纹

滚动阻力小，防侧滑性能好，适于公路高速行驶，省燃油，节约能源，经济效益好。

The tyres have small in rolling resistance and sideslip-preventing. They are suitable for driving in high speed and saving oil and beneficial.

4.50-16 6.00-13 6.00-16 7.00-16 5.00-12 6.00-15 7.50-15 5.00-14 6.00-16 7.50-16
3.00-16 6.50-14 8.25-16 5.50-13 6.50-15 7.00-15 7.00-20 7.50-20 8.25-20

HS788



八角花纹

抓着力好，自洁力好，耐湿滑性强，防侧滑，适合各种路面和气候条件。

The tyres have the features of good grasping force to ground, standing the sideslip-preventing, and the tyres are suitable for all kinds of conditions of road and climates.

9.00-20 10.00-20 11.00-20 12.00-20

注：*表示可生产标准型及加强型两种产品

轻卡胎 Light truck tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 钢 Rim		新胎充气外廓尺寸 Inflated Dimensions		最大负荷 Max Load		相应气压 Inflation Pressure
			标准轮钢 Standard rim	允许轮钢 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter	Single Load	Dual Load	
	4.50-12uLT	4.6.8	3.00B	3 1/2 J 3.00D 3.50B	127	545	415	395	400
	4.50-16LT	6	3.00B	3.00D 3.50D	127	665	325	-	250
	5.00-12uLT	6.8	3.50B	3.00D 3.00B 4J 3 1/2 J 4.00B	143	568	485	465	400
	5.00-14LT	8	3.50	3 1/2 J 4.00B	143	615	340	-	250
	5.00-16LT	8	3.50	3 1/2 J 4.00B	145	685	375	-	250
	5.50-16LT	8	4.00	4 1/2 J	165	705	425	-	250
	5.50-13LT	6.8	4J	4 1/2 J 5J	160	620	565	500	420





轻卡胎

LIGHT TRUCK TYRE

HONGSHENG RUBBER



HS388



羊角花纹

耐磨损，自洁性能好，载荷高，对路面抓着力强，噪音低，适于沙石路与公路混合行驶。

To satisfy the condition of sandstone road, the tyres have the features of standing wear and tear, and good self-cleaning. They also have good load capacity and good grasping force to ground with low noise.

4.00-8 4.00-14 4.00-12 4.50-14 6.00-1 6.00-14 6.00-15 6.00-16
7.00-20 7.50-15 7.50-16 7.50-20 11.00-20 12.00-20

HS698



越野花纹

抓着力强，防侧滑，高耐磨，超强载，适合公路与沙石路。

To satisfy the condition of use on the sandstone road and common road, the tyres have the features of good grasping force to ground, side-slip-preventing, standing wear, and good in loading capacity.

7.50-16

HS868



八角花纹

高耐磨，超强载，自洁性好，适于沙石路和普通路面行驶。

The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

4.00-16 4.50-16 5.00-14 5.00-16 5.50-16 6.50-15 6.50-14 6.50-16
7.00-15 7.00-16 8.25-16 8.25-20 9.00-16

轻卡胎
Light truck tyre

6.00-13LT	6.8		4J5J	170	655	655	570	420
6.00-14LT	6.8		4J5J	170	680	685	600	420
6.00-15LT	6.8	4.50E	4 1/2 K	170	705	720	630	420
6.00-16LT	6.8.10	4.50E	4.00E	170	730	860	755	530
6.50-14LT	6.8	4 1/2 J	5J	180	705	785	690	420
6.50-15LT	6.8	4.50E	4 1/2 K 5K 5 1/2 K 5.50F	180	730	820	720	420
*6.50-16LT	6.8.10.12	5.50F	5.00E 5.50F	185	750	975	860	530
7.00-15LT	6.8.10	5.50F	6.00G	200	750	1040	915	530
*7.00-16LT	6.8.10.12.14	5.50F	6.00G	200	775	1220	1075	630
7.50-15LT	8.10.12	6.00G	5.50F 6.50H	215	780	1370	1210	630
*7.50-16LT	6.8.10.12.14	6.00G	5.50F 6.50H	215	805	1405	1240	630
*8.25-16LT	6.8.10.12.14.16	6.50H	6.00G	235	855	1705	1500	630
9.00-16LT	6.8.10.12.14	6.50H	6.00G 7.00H	255	890	1955	1720	630



HS288



12.00-20 11.00-20 10.00-20 9.00-20

曲线花纹

滚动阻力小, 防侧滑性能好, 适于公路高速行驶, 省燃油, 节约能源, 经济效益好。

The tyres have small in rolling resistance and sideslip-preventing. They are suitable for driving in high speed and saving oil and beneficial.

HS678



9.00-20 10.00-20 11.00-20 12.00-20

八角花纹

抓着力好, 自洁力好, 耐湿滑性强, 防侧滑, 适合各种路面和气候条件。

The tyres have the features of good grasping force to ground, standing the sideslip-preventing, and the tyres are suitable for all kinds of conditions of road and climates.

HS868



7.00-20 7.50-20 8.25-20 9.00-20 10.00-20 11.00-20 12.00-20

八角花纹

耐磨耗, 自洁性能好, 载荷高, 对路面抓着力强, 噪音低, 适于沙石路与公路混合行驶。

To satisfy the condition of sandstone road, the tyres have the features of standing wear and tear, and good self-cleaning. They also have good load capacity and good grasping force to ground with low noise.

注: *表示可生产标准型及加强型两种产品

载重胎 Off-the-road tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load		相应气压 Inflation Pressure	
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter	Sinle Load	Dual Load	Sinle Load	Dual Load
			*7.00-20	10.12.14	5.5	5.50S 6.0 6.00S	200	904	1580	1385
7.50-20	8.10.12.14	6.0	6.00T 6.5 6.50T	215	935	1885	1655	810	740	
*8.25-20	10.12.14.16	6.5	6.50T 7.0 7.00T 7.0T ²	235	974	2205	1940	810	740	
*9.00-20	10.12.14.16	7.0	7.00T 7.0T ² 7.5 7.5 7.50V	259	1018	2575	2255	770	700	
*10.00-20	12.14.16.18	7.5	7.50V 8.0 8.00V 8.0V ²	278	1055	3000	2630	810	740	
*11.00-20	12.14.16.18	8.0	8.00V 8.5 8.5V ² 8.50V	293	1085	3270	2870	810	740	
12.00-20	16.18	8.5	8.50V 8.50V ² 9.00V	315	1125	3730	3270	810	740	



HEAVY-TRUCK TYRE

载重胎 On-the-road tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 钢 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load		相应气压 Inflation Pressure	
			标准轮钢 Standard rim	允许轮钢 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter	Single Load	Dual Load	Single Load	Dual Load
			10.00-20	12.14.16.18	7.5	7.50V 8.0 8.00V 8.0V5	278	1055	3000	2630
11.00-20	12.14.16.18	8.0	8.00V 8.5 8.5V5 8.50V	293	1085	3270	2870	810	740	
	12.00-20	16.18	8.5	8.50V 8.50V5* 9.00V	315	1125	3730	3270	810	740

HS118



矿山花纹

抓着力好，自洁性好，牵引性能高，负荷力强，适合松软路面、沙石地等矿山作业环境。

With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

6.50-16 7.00-16 7.50-16 8.25-16 9.00-20 10.00-20
11.00-20 12.00-20

HS998



蛇形花纹

高耐磨，超强载，自洁性好，适于沙石路和普通路面行驶。

The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

11.00-20





农业胎

Agricultural tyre

HS568



人字花纹

牵引性能好，通过性强，耐磨性强，
适合松软路面作业。

The tyres have good tractive force
and overpassing force, standing
wear, suitable for driving on the soft-
road.

8.3-20 7.50-16 8.3-24 7.50-20
6.00-12 9.50-20 9.5-24

农业胎 Agricultural tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load	相应气压 Inflation Pressure
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter		
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter		
	7.50-20	6.8	5.50F	5.00F	205	910	1020	370
	8.3-24	6.10	W7	W6	210	995	810	240
	9.5-20	6.10	W8	W7 W8H	240	950	955	280
	9.5-24	6.10	W8	W7 W8H	240	1050	1110	280
	5.00-12	6	4.00E	3.50D	145	590	280	200
	6.00-12	6	4.50E	5.00F	165	640	405	250
	5.00-14	8	4.00E	4.50	129	540	685	360
	5.00-16	8	4.00E	4.50	129	665	345	250
	550-16	8	4.00E	4.50	145	710	525	370

Agricultural tyre

农业胎 Agricultural tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load	相应气压 Inflation Pressure
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter		
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽mm Section Width	外直径mm Overall Diameter		
	4.00-8	4	3.00D	2.50C	110	425	225	300
	4.00-12	4	3.00D	2.50C	110	535	250	340
	4.00-14	4	3.00D	2.50C	110	590	270	340
	4.00-16	4	3.00D	-	110	640	300	340
	4.50-14	8	3.00D	3/2	122	625	570	360
	4.50-16	6	3.00D	3/2	122	655	615	360
	8.30-20	6	W7	W6	210	895	695	240
	7.50-16	6.8	5.50F	5.00F 5K 6.00F 6LB	205	810	650	210



德 来 来

AGRICULTURAL TYRE



工程胎

Off-the-Road tyre



叉车胎

Forklift tyre



HS668



条形花纹

耐割切,耐磨损,适合苛刻复杂的地形条件,使用寿命长。

For the complex,variable and harsh conditions of use,the tyres have the different features of wearing resistance and wearing cutted,safe and reliable.

14.00-24 17.5-25 20.5-25 23.5-25 16.00-25
26.5-25 16/70-20 18.00-25 29.5-25 16/70-24.

HS688



叉车花纹

牵引性能好,负荷高,散热性能好,适合在复杂苛刻的地形条件下运输作业。

The drawing quality is good and the tyres are high in loading and good warmtherasing.

5.00-8 6.00-9 6.50-10 7.00-12
28X9-15 8.25-12 8.25-15

工程胎 Off-the-Road tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load			相应气压 Inflation Pressure	气门嘴型号 Valve Size
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽/mm Section Width	外直径/mm Overall Diameter	65	50	15		
							km/h	km/h	km/h		
17.5-25	12	14.00/1.5	—	445	1350	3120	3750	4190	280	Z ₁ -01-8	
17.5-25	14	14.00/1.5	—	445	1350	3330	4010	4480	280	Z ₁ -01-8	
17.5-25	20	14.00/1.5	—	445	1398	-	-	5440	280	Z ₁ -01-8	
20.5-25	16	17.00/2.0	—	520	1490	4280	5170	5770	350	Z ₁ -01-6	
20.5-25	20	17.00/2.0	—	520	1548	4880	5900	6580	350	Z ₁ -01-6	
23.5-25	16	19.5/2.5	—	595	1615	5170	6250	6970	350	Z ₁ -01-8	
23.5-25	20	19.5/2.5	—	595	1673	5530	6680	7460	280	Z ₁ -01-8	
14.00-24	16/24	10.00	—	375	1370	4760/6030		420/630	Z ₁ -01-8		
16.00-25	20/28	11.25/2.0	—	430	1546	6220/7360		420/560	Z ₁ -01-8		
26.5-25	16/20	22.00/3.0	—	675	1750	11500/13200		275/350	Z ₁ -01-8		
16/70-20	10/14	13.00	—	410	1075	4200/5150		325/450	Z ₁ -01-8		
18.00-25	20/28	13.00/2.5	—	495	1615	7230/8810		350/490	Z ₁ -01-8		
29.5-25	16/22	25.00/3.5	—	750	1875	12900/15000		250/325	Z ₁ -01-8		
16/70-24	10/14	13.00	—	410	1175	4750/5650		325/4.50	Z ₁ -01-8		

工程胎 Forklift tyre	轮胎规格 Tyre Size	层级 Ply Rating	轮 辋 Rim		新胎充气外缘尺寸 Inflated Dimensions		最大负荷 Max Load				相应气压 Inflation Pressure	气门嘴型号 Valve Size
			标准轮辋 Standard rim	允许轮辋 Permitted rim	断面宽/mm Section Width	外直径/mm Overall Diameter	10	25	40	50		
							km/h	km/h	km/h	km/h		
5.00-8	8.10	3.50D	3.00D	137	470	950	765	665	595	800	TZ-45	
6.00-9	10	4.00E	4.50E	160	540	1410	1135	985	885	850	TZ-45	
6.50-10	10	5.00F	5.50F	175	590	1545	1245	1080	970	775	TZ-45	
7.00-9	10	5.00S	-	190	590	1865	1500	1300	1170	850	TZ-45	
7.00-12	12	5.00S	5.50S	190	675	2225	1790	1505	1400	850	TZ-45	
28X9-15	12,14,16	7.0	7.00T	222	710	3515	2705	2180	1850	900	-	
8.25-12	12	6.5	5.00S	235	765	2950	2375	2060	1855	750	TZ-50	
8.25-15	14	6.5	6.50T	235	840	3230	2600	2255	2030	800	TZ-50	