


S626



Size	Load Range	Load Index	Tread Depth		Max Speed (mile/h)	Speed Rate	Static Loadload Radius		Overall Diameter		Overall Width		Meas RIM	Min Dual Spacing		Single Max i.p.		dual Max i.p.		Max load (single/dual)		Revs Per Mile
			X/32	mm			ins.	mm	ins.	mm	ins.	mm		ins.	mm	psi	kpa	psi	kpa	lbs	kg	
11R22.5	16PR/H	148/145	18	14	75	L	19.26	489	41.50	1054	10.94	278	8.25	12.52	318	123	850	123	850	6940/6390	3150/2900	502
9.00R20	16PR/H	144/142	17	13.5	70	K	18.79	477	40.2	1021	10.04	255	7.00	12.05	306	130	900	112	770	6170/5840	2800/2650	517
10.00R20	16PR/H	146/143	17	14	70	K	19.30	490	41.38	1051	10.75	273	7.50	12.91	328	120	840	112	770	6615/5800	3000/2630	502
11.00R20	16PR/H	149/145	18	14.5	70	K	19.93	506	42.83	1088	11.3	287	8.00	13.62	346	120	840	120	840	7210/6325	3270/2870	485

Structure



- For all round fitment to coaches and trucks.
- Designed for highway and improved road surfaces.
- Multiple rib design features excellent wet traction and lateral stability.