

S815



Size	Load Range	Load Index	Tread Depth		Max Speed (mile/h)	Speed Rate	Static Load Radius		Overall Diameter		Overall Width		Meas RIM	Min Dual Spacing		Single Max i.p.		Dual Max i.p.		Max load (single/dual)		Revs Per Mile
			X/32	mm			ins.	mm	ins.	mm	ins.	mm		ins.	mm	psi	kpa	psi	kpa	lbs	kg	
11R22.5	16PR/H	148/145	23	18.5	75	L	19.39	493	41.65	1058	10.94	278	8.25	12.52	318	123	850	123	850	6940/6390	3150/2900	499
11.00R20	16PR/H	149/145	22	17.0	70	K	19.93	506	42.83	1088	11.54	293	8.00	13.62	346	122	840	112	770	7210/6325	3270/2870	485
315/80R22.5	18PR/J	156/150	22	17.5	75	L	19.86	504	42.76	1086	12.09	307	9.00	13.82	351	123	850	123	850	8820/7385	4000/3350	486
315/80R22.5	16PR/H	154/150	22	17.5	80	M	19.86	504	42.76	1086	12.09	307	9.00	13.82	351	120	825	120	825	8270/7385	3750/3350	486
275/70R22.5	16PR/H	148/145	21	17.5	70	K	17.69	449	38.11	968	10.71	272	8.25	12.24	311	130	900	130	900	6940/6395	3150/2900	545

Structure

strong resistance to wear

sturdy carcass provides maximum load



good durability of rim

- Premium all position tire for steer, trailer and mixed service applications.
- Designed for both on and off road conditions.
- Designed with premium tread depths of 22/32" for longer wear.
- Tread compound designed to resist chipping and tread laceration protects the tire in severe on/off road conditions.