



## TB516S RADIAL OFF-THE-ROAD TIRES

With deepen traction pattern.  
 Excellent traction.  
 Excellent puncture resistance.  
 Suitable for the severe grinding condition.  
 Stable handling.  
 Low heat build-up at high speed.

Size	Code	Star rating	Load Index	Standard Rim	Overall dimensions of new tyre inflated ( mm )				Max.Load (kg)	Standard Pressure(bar)	Max.Speed (km/h)	Tubeless	Tread depth
					Overall diameter±3%		Section Width	+6%					
					Normal pattern	super pattern							
14.00R24	E-4	☆	157/153	10.00W	1368	1418	375	4125/3650	4.75/3.75	50/40	TL	36	
		☆☆	186/168					9500/5600	8.0/6.5	10/50			
		☆☆☆	188/169					10000/5800	9.5/7.0	10/50			
14.00R25	E-4	☆	157	10.00/1.5	1368	1418	375	4125	4.75	50	TL	36	
		☆☆	186/168					9500/5600	8.0/6.5	10/50			
		☆☆☆	188/169					10000/5800	9.5/7.0	10/50			
18.00R25	E-4	☆	194/168/176	13.00/2.5	1617	1673	498	11800/5600/7100	5.50/3.50/4.75	10/40/50	TL	46	
		☆☆	204/185					16000/9250	8.25/7.00	10/50			
		☆☆☆	219/216					24300/22400	9.95	5/10			

Note: load index,Max load(kg),the figure between left and right of slant is accordance with that of standard pressure(bar) and Max speed(km/h).

With deepen traction pattern.  
 Excellent traction.  
 Excellent puncture resistance.  
 Suitable for the severe grinding condition.  
 Stable handling.  
 Low heat build-up at high speed.