



TR638H FREEWAY



- ★ Applicable for the front wheels of trucks on city & good roads.
- ★ This pattern has an excellent resistance to uneven wearing and with higher driving mileage.
- ★ Applicable for higher speed driving and with lower noise.



TR656H FREEWAY



- ★ Suitable to all the wheels of buses and front wheels of trucks on city and good roads.
- ★ Excellent anti-irregular-wear performance, and high mileage.
- ★ Suitable to high speed running and with lower noise emission.



TR657H FREEWAY



- ★ Applicable for driving wheels of trucks on express way and city roads.
- ★ This pattern tire offers a good pulling force.
- ★ Applicable for high speed driving and with long life.

	Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire Inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min. Dual Tire Space (mm)	Alternative Rim
				Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual		
TR638H	7.50R20	TT	14	130	128	12.0	L	6.0	215	935	435	1900	1800	830	254	6.5, 6.50T	
	8.25R20	TT	14	136	134	12.0	L	6.5	236	974	452	2240	2120	830	278	6.50T, 7.0, 7.00T	
TR656H	8.5R17.5	TL	12	121	120	11.5	M	6.00	210	800	376	1450	1400	625	242	6.75	
	8R19.5	TL	12	124	122	12.5	K	6.00	203	859	402	1600	1500	760	231	6.75	
	255/70R22.5	TL	16	140	137	13.5	M	7.50	255	930	435	2500	2300	830	287	8.25	
	275/70R22.5	TL	16	148	145	14.5	L	8.25	276	958	446	3150	2900	860	311	9.00	
	LT235/85R16	TL	14	126	123	14.0	L	6.50	235	806	373	1700	1550	750	273	6J, 7J	
TR657H	9.00R20	TT	14	141	139	16.0	L	7.0	259	1019	471	2575	2430	790	306	7.00T, 7.5	
			16	144	142							2800	2650	900			
			18	144	142							2800	2650	900			
	10.00R20	TT	16	146	143	17.0	L	7.5	278	1054	486	3000	2725	830	328	7.50V, 8.0	
			18	149	146							3250	3000	930			
	11.00R20	TT	16	150	147	18.0	L	8.0	293	1085	499	3350	3075	830	346	8.00V, 8.5	
			18	152	149							3550	3250	930			
	12.00R20	TT	18	154	151	18.0	L	8.5	315	1125	516	3750	3450	830	372	8.50V, 9.0	
			18	154	151							3750	3450	830			
	10R22.5	TL	14	141	139	20.0	M	7.50	254	1019	476	2575	2430	790	290	6.75	
	11R22.5	TL	14	144	142	21.5	M	8.25	279	1054	491	2800	2650	720	318	7.50	
			16	146	143							3000	2725	830			
	12R22.5	TL	16	150	147	21.5	L	9.00	300	1085	504	3350	3075	830	342	8.25	
			18	154	150							3750	3350	850			
13R22.5	TL	16	154	150	21.5	L	9.75	320	1124	521	4000	3350	875	350	9.00		
		18	156	150							3000	2725	720				
11R24.5	TL	14	146	143	21.5	M	8.25	279	1104	516	3000	2725	720	318	7.50		
		16	149	146							3250	3000	830				
295/75R22.5	TL	14	144	141	21.5	M	9.00	298	1014	474	2800	2575	760	335	8.25		
		16	146	143							3000	2725	830				
285/75R24.5	TL	14	144	141	21.5	M	8.25	283	1050	493	2800	2575	760	318	—		
		16	147	144							3075	2800	830				