



## TR675A GENERAL



- ★ Designed for all wheels of buses and front wheels of trucks.
- ★ With Extra anti-side skid and wet skid resistance.
- ★ Super traction and braking performance.
- ★ High load and high speed.



## TR676



- ★ Suitable to all the wheels of buses and the steer wheels of trucks on highway and city roads.
- ★ Excellent anti-irregular-wear performance, and high mileage.
- ★ Suitable to high speed running with lower noise emission.



## TR677H FREEWAY



- ★ Special for trailers.
- ★ With extra anti-side skid and wet skid resistance.
- ★ Light weight and low rolling resistance.
- ★ High load and high speed.

	Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min Dual Tire Space (mm)	Alternative Rim
				Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual		
TR675A	245/70R19.5	TL	14	133	131	12.5	L	7.50	248	839	391	2060	1950	760		279	6.75
			16	135	133							2180	2060	830			
	265/70R19.5	TL	14	140	138	13.0	L	7.50	262	867	402	2500	2360	850		295	8.25
18			143	141	2725							2575	850				
TR676	11R22.5	TL	14	144	142	10.5	M	8.25	279	1054	491	2800	2650	720		318	7.50
	11R24.5	TL	14	146	143	10.5	M	8.25	279	1104	516	3000	2725	720		318	7.50
			16	149	146							3250	3000	830			
	295/75R22.5	TL	14	144	141	10.5	M	9.00	298	1014	474	2800	2575	760		335	8.25
285/75R24.5	TL	14	144	141	10.5	M	8.25	283	1050	493	2800	2575	760		318	—	
		16	147	144							3075	2800	830/760				
TR677H	10.00R20	TT	16	146	143	10.5	L	7.5	278	1054	486	3000	2725	830		328	7.50V, 8.0
	11.00R20	TT	16	150	147	11.0	L	8.0	293	1085	499	3350	3075	830		346	8.00V, 8.5
	11R22.5	TL	14	144	142	10.5	L	8.25	279	1054	491	2800	2650	720		318	7.50
			16	146	143							3000	2725	830			
12R22.5	TL	16	150	147	11.0	L	9.00	300	1085	504	3350	3075	830		342	8.25	