



TR695H FREEWAY



- ★ Designed for front wheels and all wheels.
- ★ With extra anti-side skid and wet skid resistance.
- ★ Super traction and braking performance.
- ★ High load and high speed.



TR696A GENERAL



- ★ Applicable for the front wheels of trucks on city and good roads.
- ★ This pattern tire with higher driving mileage.
- ★ Applicable for higher speed driving with lower noise.



TR697



- ★ Applicable for all the wheels of trucks on city and unpaved roads.
- ★ This pattern tire with excellent pulling force.
- ★ With a very long life.

	Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire Inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min. Dual Tire Space (mm)	Alternative Rim	
				Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual			
TR695H	9.00R20	TT	14	141	139	14.5	L	7.0	259	1019	471	2575	2430	790		306	7.5, 7.00T	
				16	144							142	2800	2650	900			
				16	144							142	2800	2650	900			
	10.00R20	TT	16	146	143	14.5	L	7.5	278	1054	486	3000	2725	830		328	8.0, 7.50V	
				18	149							146	3250	3000	930			
	11.00R20	TT	16	150	147	15.5	L	8.0	293	1085	499	3350	3075	830		346	8.5, 8.00V	
				18	152							149	3550	3250	930			
	12.00R20	TT	18	154	151	16.5	L	8.5	315	1125	516	3750	3450	830		372	8.50V, 9.0	
				18	154							151	3750	3450	830			
	10R22.5	TL	14	141	139	14.5	M	7.50	254	1019	476	2575	2430	790		290	6.75	
11R22.5	TL	14	144	142	14.5	M	8.25	279	1054	491	2800	2650	720		318	7.50		
			16	146							143	3000	2725	830				
12R22.5	TL	16	150	147	15.5	L	9.00	300	1085	504	3350	3075	830		342	8.25		
			16	154							150	3750	3350	850				
13R22.5	TL	16	154	150	16.5	L	9.75	320	1124	521	3750	3350	875		350	9.00		
			18	156							150	4000	3350	875				
TR696A	11R22.5	TL	14	144	142	14.5	M	8.25	279	1054	491	2800	2650	720		318	7.50	
				16	146							143	3000	2725	830			
	11R24.5	TL	14	146	143	14.5	M	8.25	279	1104	516	3000	2725	720		318	7.50	
				16	149							146	3250	3000	830			
	295/75R22.5	TL	14	144	141	14.5	M	9.00	298	1014	474	2800	2575	760		335	8.25	
				16	146							143	3000	2725	830			
285/75R24.5	TL	14	144	141	14.5	M	8.25	283	1050	493	2800	2575	760		318	—		
			16	147							144	3075	2800	830/760				
TR697	385/65R22.5	TL	20	160	—	16.5	J	11.75	389	1072	494	4500	—	900	—	12.25		
			158			L												