



TR616A GENERAL



- ★ Design of tyre property is adequate for all the wheels of long-distance trucks and buses .
- ★ The time emphasizing guaranteeing long-distance and high-speed running performance, it's compatible with adequate overloading property, grade of tire speed has been elevated to level M.
- ★ Improved wear-resistance property in high temperature.
- ★ It has reliable operating property.



TR618A GENERAL



- ★ Design of tyre property is adequate for all the wheels of long-distance trucks and buses .
- ★ The time emphasizing guaranteeing long-distance and high-speed running performance, it's compatible with adequate overloading property, grade of tire speed has been elevated to level M.
- ★ Improved wear-resistance property in high temperature.
- ★ It has reliable operating property.



TR618-IH FREEWAY



- ★ Design of tyre property is adequate for all the wheels of long-distance trucks and buses .
- ★ The time emphasizing guaranteeing long-distance and high-speed running performance, it's compatible with adequate overloading property, grade of tire speed has been elevated to level L.
- ★ Improved wear-resistance property in high temperature.
- ★ It has reliable operating property.

Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min. Dual Tire Space (mm)	Alternative Rim	
			Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual			
TR616A	9.00R20	TT	14	141	139	15.0	K	7.0	259	1019	471	2575	2430	790	790	306	7.00T, 7.5
			16	144	142							2800	2650	900	900		
	10.00R20	TT	16	146	143	16.0	K	7.5	278	1054	486	3000	2725	830	830	328	7.50V, 8.0
			18	149	146							3250	3000	930	930		
11.00R20	TT	16	150	147	16.5	K/L	8.0	293	1085	499	3350	3075	830	830	346	8.5, 8.00V	
		18	152	149							3550	3250	930	930			
12.00R20	TT	18	154	151	17.0	K/L	8.5	315	1125	516	3750	3450	830	830	372	8.50V, 9.0	
		18	154	151							3750	3450	830	830			
TR618A	8.25R16LT	TT	14	126	122	12.5	M	6.50H	235	855	397	1700	1500	670	278	6.00G, 6.5	
	9.00R20	TT	14	141	139	15.0	K	7.0	259	1019	471	2575	2430	790	306	7.00T, 7.5	
			16	144	142							2800	2650	900			
			16	144	142							2800	2650	900			
	10.00R20	TT	16	146	143	16.0	K/L	7.5	278	1054	486	3000	2725	830	328	7.50V, 8.0	
			18	149	146							3250	3000	930			
11.00R20	TT	16	150	147	16.5	K/L	8.0	293	1085	499	3350	3075	830	346	8.00V, 8.5		
		18	152	149							3550	3250	930				
12.00R20	TT	18	154	151	17.0	K/L	8.5	315	1125	516	3750	3450	830	372	8.50V, 9.0		
		18	154	151							3750	3450	830				
TR618-IH	9.00R20	TT	14	141	139	13.5	L	7.0	259	1019	471	2575	2430	790	306	7.00T, 7.5	
			16	144	142							2800	2650	900			
			16	144	142							2800	2650	900			
	10.00R20	TT	16	146	143	14.5	L	7.5	278	1054	486	3000	2725	830	328	7.50V, 8.0	
			18	149	146							3250	3000	930			
	11.00R20	TT	16	150	147	15.0	L	8.0	293	1085	499	3350	3075	830	346	8.00V, 8.5	
18			152	149	3550							3250	930				
12.00R20	TT	18	154	151	15.5	L	8.5	315	1125	516	3750	3450	830	372	8.50V, 9.0		
		18	154	151							3750	3450	830				