



TR660A GENERAL



- ★ Suitable to all the wheels of buses or the steer wheels of trucks on highway and city roads.
- ★ Excellent anti-irregular-wear performance, and high mileage.
- ★ Suitable to high speed running and with lower noise emission.



TR665A GENERAL



- ★ Applicable for the front wheels of trucks on city & good roads.
- ★ This pattern has an excellent resistance to uneven wearing and with higher driving mileage.
- ★ Applicable for higher speed driving and with lower noise.

	Size	Tube	PR		Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire inflated Dimensions (mm)		Static Radius Under Load (mm)	Max Load(kg)		Pressure (kPa)		Min Dual Tire Space (mm)	Alternative Rim
			Single	Dual	Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual		
TR660A	8.25R20	TT	12	132	127	12.5	L	6.5	236	974	452	2015	1770	740/670		278	7.0	
			14	136	134							2240	2120	830				
	8R22.5	TL	14	130	128	12.5	M	6.00	203	935	440	1900	1800	830		231	6.75	
TR665A	10.00R20	TT	16	146	143	14.5	K	7.5	278	1054	486	3000	2725	830		328	8.0, 7.50V	
			18	149	146							3250	3000	930				
	9R22.5	TT	14	136	134	13.0	L	6.75	229	974	457	2240	2120	830		261	7.50	
	10R22.5	TT	14	141	139	14.0	M	7.50	254	1019	476	2575	2430	790		290	6.75	
	318/80R22.5	TL	18	154	151	14.5	M	9.00	312	1076	500	3750	3450	830		351	9.75	
20			157	154	L		4125					3750	900					