



TR678H FREEWAY



- ★ Suitable for all wheels of heavy duty trucks on urban and unpaved road.
- ★ Wider section and low all series pattern for special usage assisting in excellent water drainage and improving traction.
- ★ Assorted with monotype product which can reduce fuel consumption and tire cost.



TR679A GENERAL



- ★ Applicable for the front wheels of trucks on city and good roads.
- ★ This pattern has an excellent resistance to uneven wearing and with higher driving mileage.
- ★ Applicable for higher speed driving with lower noise.



TR680



- ★ Superior anti side skid performance , high speed straight wide groove, load balance, wear well-proportioned
- ★ Special tread compound, low heat build-up, anti-abrasive
- ★ Longitude straight groove and special compound, low rolling resistance, low fuel consumption
- ★ Applicable for the trailer wheel of van and tractor on freeway, urban and rural road

	Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min. Dual Tire Space (mm)	Alternative Rim
				Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual		
TR678H	425/65R22.5	TL	18	162	164	16.5	K	12.25	422	1124	515	4750	—	760	—	13.00	
				20			J					5000	—	830			
TR679A	11.00R22	TT	16	152	149	15.5	K	8.0	293	1135	525	3550	3250	830	346	8.00V, 8.5	
TR680	295/60R22.5	TL	18	149	146	14.5	L	9.00	292	926	—	3350	3075	900	329	9.00	