



TR689A GENERAL



- ★ Designed mainly for driving wheels of heavy duty trucks.
- ★ With extra anti-side skid and wet skid resistance.
- ★ Super traction and flotation performance.
- ★ High load and high speed.



TR690E WORSE ROAD, MINE ROAD



- ★ Shoulder block pattern and middle longitude pattern, good driving and braking performance
- ★ Open wide groove design, good self-cleaning and cooling
- ★ Massiness block pattern, good anti-abrasive
- ★ Applicable for the driving wheel of dump truck, van and tractor on rural, building site and mine road

Size	Tube	PR	Load Index		Tread Depth (mm)	Speed Rating	Rim Width	New Tire Inflated Dimensions (mm)		Static Radius Under Load (mm)	Max. Load(kg)		Pressure (kPa)		Min. Dual Tire Space (mm)	Alternative Rim
			Single	Dual				Section Width	Overall Diameter		Single	Dual	Single	Dual		
TR689A	8.25R16LT	TT	14 16	126 128	122 124	14.5	M	6.50H	235	855	397	1700 1800	1500 1600	670 770	278	6.5
	215/75R17.5	TL	16	135	133	15.5	L	6.00	211	767	360	2180	2060	860	237	6.75
	235/75R17.5	TL	16 18	141 143	140 141	15.5	J J	6.75	233	797	373	2575 2725	2500 2575	850 860	262	7.50
	225/70R19.5	TL	14	128	126	17.0	L	6.75	226	811	382	1800	1700	760	254	6.00
	245/70R19.5	TL	14 16	133 135	131 133	17.0	L	7.50	248	839	391	2060 2180	1950 2060	760 830	279	6.75
TR690E	8.25R16LT	TT	16	128	124	12.5	K	6.50H	235	855	397	1800	1600	770	278	6.00G,6.5
	9.00R20	TT	16	144	142	15.0	K	7.0	259	1019	471	2800	2650	900	306	7.00T,7.5
			16 ***	144	142							2800	2650	900		
	10.00R20	TT	16	146	143	16.0	K	7.5	278	1054	486	3000	2725	830	328	7.50V,8.0
			18	149	146							3250	3000	930		
			18 ****	149	146							3250	3000	930		
	11.00R20	TT	16	150	147	17.0	K	8.0	293	1085	499	3350	3075	830	346	8.00V,8.5
			18	152	149							3550	3250	930		
18 ****			152	149	3550							3250	930			
12.00R20	TT	18	154	151	18.0	K	8.5	315	1125	516	3750	3450	930	372	8.50V,9.0	
		18 ***	154	151							3750	3450	830			
		18 ****	154	151							3750	3450	830			